

CLAIMS

5 We claim:

1. An oligonucleotide synthesizer comprising a reaction chamber and a lid, wherein in an open position, said lid provides a substantially enclosed ventilated workspace.

10

2. A method of protecting an operator of an oligonucleotide synthesizer comprising channeling ambient air away from an operator toward an interior space of said synthesizer.

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

3. An apparatus comprising, in combination, an oligonucleotide synthesizer and a venting hood.

4. An apparatus configured for production of oligonucleotides, wherein said apparatus comprises a venting component configured to draw air away from a reaction chamber of said apparatus.

5. A system comprising a plurality of oligonucleotide synthesizers of Claim 1.

6. The system of Claim 5, wherein said system comprises 100 or more of said synthesizers.

7. A system comprising a plurality of apparatuses of Claim 3.

8. The system of Claim 7, wherein said system comprises 100 or more of said apparatuses.

9. A system comprising a plurality of apparatuses of Claim 4.

10. The system of Claim 9, wherein said system comprises 100 or more said
5 apparatuses.

11. A polymer synthesizer comprising a ventilated workspace.

12. The polymer synthesizer of Claim 11, wherein said polymer synthesizer is
10 a nucleic acid synthesizer.

13. The polymer synthesizer of Claim 11, wherein said synthesizer comprises
a top enclosure, said top enclosure comprising a top plate with a ventilation opening,
wherein said top enclosure is configured for attachment to a top cover of a synthesizer to
15 form a primarily enclosed space over said top cover.

14. The polymer synthesizer of Claim 11, wherein said synthesizer comprises
a base, said base comprising a primarily enclosed space and a ventilation opening.

15. A top enclosure comprising a top plate with a ventilation opening, wherein
said top enclosure is configured for attachment to a top cover of a synthesizer to form a
primarily enclosed space over said top cover.
20

16. The top enclosure of Claim 15, wherein said top plate is configured for
25 attachment to a ventilation tube such that air in said primarily enclosed space may be
drawn through said ventilation opening into said ventilation tube.

17. The top enclosure of Claim 15, wherein said top plate further comprises an
outer window, and wherein said ventilation opening is formed in said outer window.
30

18. The top enclosure of Claim 15, wherein said top enclosure further comprises at least four sides.

19. The top enclosure of Claim 15, wherein said top cover further comprises a ventilation slot.

20. A system comprising;

a) a ventilation tube, and

b) a lid enclosure comprising; a) a top cover with a ventilation slot,

and b) a top enclosure comprising a top plate with a ventilation opening, wherein said top enclosure is attached to said top cover to form a primarily enclosed space over said top cover.

21. The system of Claim 20, further comprising a vacuum source.

22. The system of Claim 20, wherein said vacuum source comprises a centralized vacuum system.

23. A kit comprising;

a) a top enclosure comprising a top plate with a ventilation opening, wherein said top enclosure is configured for attachment to a top cover of a synthesizer to form a primarily enclosed space over said top cover, and

b) a printed material component, wherein said printed material component comprises written instruction for installing said top enclosure onto said top cover.